

# whisper-print time clock



The Model 800P Time Clock provides library-quiet printing of employees' in and out times, along with the day-of-week for each transaction. While the default print settings are suitable for most workplaces, administrators can set preferences for printing 12-hr time with AM/PM indicator, or 24-hr (military) time; Minutes can be printed in hundredths of an hour to simplify tallies; Day-of-week can be printed in English, Spanish or French. The 800P can automatically adjust for Daylight Savings Time, and maintains its date, time and user preferences during power failures.

Allowing single-handed operation, Latham's Tru-Align™ feature provides visual and audio direction, automatically triggers an imprint when a Time Card is properly inserted, and ensures that the imprint only occurs within the boundaries of the Time Card's print cell. Tru-Align eliminates partial over-printing in adjacent cells that can make print unreadable.

Administrators never need to open the "steel tough"® enclosure, as the 800P's printer is clean and maintenance-free, with no ink pad to fill or ribbon to replace. The 800P is compatible with Latham E8 time cards.

## 800P

### THERMAL PRINTING TIME RECORDER



**Tru-Align™** feature ensures correct alignment for every punch!

### REQUIRES NO RIBBONS OR INK



## LATHEM

## FEATURES

- Direct thermal print eliminates ribbons and ink.
- Automatic True-Align™ eliminates misprinting.
- Whisper-Print™ technology offers quiet punches.
- Prints day of week and time (AM/PM or 24 hour).
- Keeps time & settings during power loss.
- Automatic Daylight Saving Time change.
- Table top or wall mount option. (Wall bracket included)
- Includes 25 E8 time cards.
- Made in USA.
- 1 year warranty.

## SPECIFICATIONS

Dimensions: 5 1/3 "H x 6"W x 3"D

13.5cm H x 15.2cm W x 7.6cm D

Weight: 5.0 lbs (2.3 kg)

Display: LCD

Housing: Electro-Galvanized Steel with Powder-Paint Coating

Line Power: 120vAC, 80mA typical

220vAC, 80mA typical

50 / 60 Hz

Memory: BR2325 Coin-Cell Lithium Battery

(change the battery every 7 years-recommendation)

Environment: 32° to 140° F (0° to 60° C)

95% Relative Humidity (non-condensing)

Timecard Storage: 150° F (65°C) maximum temperature

Note: The E8-B timecards are sensitive to temperature and should always be stored in a cool dry location; preferably out of exposure to direct sun light. Storage temperature should not exceed 150°F (65°C).

## E8 SAMPLE TIME CARD

Name		No.	
Pay Period Ending			
EXTRA TIME		REGULAR TIME	
Day 1 Hrs.	IN	Mo	8:00A
	OUT	Mo	12:00P
	IN	Mo	1:00P
	OUT	Mo	5:00P
Day 2 Hrs.	IN	Tu	8:00A
	OUT	Tu	12:00P
	IN	Tu	1:00P
	OUT	Tu	5:00P
Day 3 Hrs.	IN	We	8:00A
	OUT	We	12:00P
	IN	We	1:00P
	OUT	We	5:00P
Day 4 Hrs.	IN	Th	8:00A
	OUT	Th	12:00P
	IN	Th	1:00P
	OUT	Th	5:00P
Day 5 Hrs.	IN	Fr	8:00A
	OUT	Fr	12:00P
	IN	Fr	1:00P
	OUT	Fr	5:00P
		Sa	8:00A

  

Reg Hrs. _____	Rate _____
Extra Hrs. _____	Rate _____
D. Fed. Tax. ....	
D. State Tax. ....	
U. Soc. Sec. Tax. ....	
T. Medicare. ....	
O. Insurance. ....	
N. Miscellaneous	



The Tru-Align feature automatically prints the time card when the cell is aligned and indicates successful punch with a green light.



**LATHEM**

**Lathem Time • Atlanta, Georgia USA • [www.lathem.com](http://www.lathem.com)**

This information is subject to change without notice. Copyright © 2009 Lathem Time Corporation. Printed in USA.

"Whisper Print", "Tru-Align" and "Steel-Tough" are registered trademarks of Lathem Time Corp.

\*"Whisper Print" and "Tru-Align" technologies are Patent-Pending. Lathem and the Lathem logo are registered trademarks of Lathem Time Corporation.